

POLIESTERE
TESTURIZZATO LUCIDO
DTEX 56/48/150 S



TOT SRL
stock service filati

POLIESTERE TESTURIZZATO LUCIDO DTEX 56/48/150 S - 2



IDROFIX



FONTE



MALLO



CARAIBI



CORDA



VERDE



COGNAC



ACIDO



TAUPE



GREEN



TITANO



MUSCHIO



GRES



KIWI



PIOMBO



VERDE MARCIO



PALISSANDRO



PETROLIO



NERO



GHIANDA

POLIESTERE TESTURIZZATO LUCIDO DTEX 56/48/150 S - 3



RUGGINE



CONCHIGLIA



CROCCANTE



GLICINE



ACQUAVITE



CARDINALE



ANANAS



PERVINCA



ZUCCA



CELESTE



ARANCIO



AVIO



BEGONIA




ARNO



ROSSO



BLU ELETTRICO



FIAMMA



PROFONDO



VINACCIA



UVA

POLIESTERE

Polyester

Tinto con coloranti dispersi.

Si garantiscono trattamenti ad umido che non superino la temperatura di 70°. Oltre tale condizione, si consigliano prove preliminari.

Dyed with reactive dyestuff or indathrene.

We guarantee damp treatment which will not get over the temperature of 70°. In addition to this condition, we suggest previous tests.

Solidità minime garantite:

Lowest fastness granted:

	LUCE <i>light</i>	LAVAGGIO A 50° <i>washing at 50°</i>	TERMOFISSAGGIO A 160°A SECCO <i>thermo fixing at 160° dr</i>
COLORI CHIARI <i>light colours</i>	4	5	4/5
COLORI MEDI <i>medium colours</i>	4	4/5	4/5
COLORI SCURI <i>dark colours</i>	4/5	4/5	4

I valori riportati si riferiscono al cambiamento di tono.

The a.m. values are referred to the change of the colour's tone.

Gli stingimenti sulle fibre accompagnatorie vanno valutati di volta in volta in funzione delle condizioni di lavorazione e al tipo di fibra ma comunque non sono inferiori al valore 3/4.

The fading on the accompanying fibres must be valuated every time according to the working conditions and to the kind of fibre, but anyhow it will not be less than value 3/4.

Per qualsiasi altra esigenza di tipo tecnico si consiglia di informarsi preventivamente.

For any other technical requirement please ask information in advance.

t.o.t. srl

tessimenti e orditi tinti stock service

Via Ticino, 1/B - 22070 Casnate con Bernate (CO)

Tel. 031.473021 - Fax 031.471756 - e-mail: info@totsrl.it - www.totsrl.it